

# RAMMER RPV22R ROTATING PULVERIZER



## HEAT TREATED PINS AND BUSHINGS

Hardened parts are more wear resistant, extending their working life and lowering owning and operating costs

## BOLT ON CUTTING BLADES

Field replaceable and adjustable cutter blades minimize downtime and significantly increase the working life of wear parts

## SPEED VALVE

Shorter working cycles increase productivity

## HYDRAULIC ROTATION WITH PROTECTION VALVE

The protected rotation system allows precision tool placement, lowering/reducing owning and operating costs.

## FIELD REPLACEABLE WEAR PARTS

Minimise downtime as there is no need for welding/rebuilding

## GRATED JAW DESIGN

The fixed jaw allows crushed material to pass through increasing productivity

## RPV ROTATING PULVERIZERS

The Rammer RPV Rotating Pulverizer range is ideally suited to a wide range of primary and secondary demolition duties. The built in rotation that comes as standard on RPV Rotating range allows for added maneuverability for fast and effective material separation.

**Rammer**<sup>®</sup>

# RPV22R

## SPECIFICATIONS

Working weight, kg	2000
Operating pressure, bar	300-350
Oil flow range, l/min	180-200
Rotation working pressure, bar	130-150
Rotation oil flow, l/min	30-40
Blade length, mm	180
Replaceable tips	yes
Carrier weight, range, ton	18-26

Height 2130 mm

Jaws depth 730 mm

Max. jaws opening 750 mm

Jaws width 475 mm

Sandvik Mining and Construction Oy  
Taivalkatu 8, P.O.Box 165  
FI-15101 Lahti, Finland  
Phone Int. +358 205 44 151  
[www.rammer.com](http://www.rammer.com)

**Ram  
mer**<sup>®</sup>