

SHAFTS SCREENERS

MB-HDS214











SPECIFICATIONS

<u>(1</u>	Recommended excavator	ton	9 - 13
	Recommended backhoe loader/loader*	ton	8 - 13
~	Recommended skid steer loader*	ton	4 - 10
	Weight	ton	0,82
	Load capacity	m³	0,40
	Pressure	bar	200 - 250
	Oil flow rate**	I/min	75 - 120
	Size A	mm	1380
	Size B	mm	1125
	Size C	mm	950

^{*} Please verify machine's Rated Operating Capacity

SHAFT KIT

KIT

	RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration	
•	RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction	
	RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil	
5	RC Compost kit	36.5 mm	Shredding foliage and small branches Composting	

ADJUSTMENT*

APPLICATION

OPTIONAL ACCESSORIES

RQ8	Sifting kit	RQ20 Sifting kit	
RQ50	O Sifting kit	RM Mixer kit	
RE8 I	Fine sifting kit	RE16 Fine sifting kit	
RC Co	ompost kit	Shaft holder	

APPLICATION AREAS







Urban construction site



Enclosed spaces







Maintaining landscape and agricultural areas

^{**} The minimum hydraulic flow rate value must be alongside the required operating pressure

 $^{^{\}ast}$ Shafts in closed position.