

# HSL SERIES

## STANDARD FLOW FORESTRY MULCHER

Flow through your workday while using any level skid steer and without sacrificing toughness. This residential contractor's favourite works out-of-the-box for standard flow options. If your carrier flow increases, the mulcher can match it with a simple motor upgrade.



SCAN HERE  
TO VIEW IN  
3D + AR



**60"**  
CUTTING WIDTH

**STANDARD FLOW**  
EXCAVATORS



PROMACEQUIPMENT.CA / HSL

## KEY SPECS:

## HSL 60

	SKID STEER RATING	STANDARD FLOW
	CUT WIDTH (INCHES)	60
	MIN. WEIGHT (POUNDS)	1800
	STD. MOTOR TYPE	VARIABLE DISPLACEMENT
	STD. MOTOR SIZE (CC)	55
	AVG. FLOW RANGE (GPM)	20-37
	MIN. PRESSURE (PSI)	2900
	SUGGESTED DRUM SPEED (RPM)	2600
	SUGGESTED MIN. CARRIER (HP)	50

## RESIDENTIAL CONTRACTOR'S CHOICE



## BUILD & COMPONENTS

### STANDARD

"FIXED TOOTH ROTOR"  
DRUM TYPE W/ LIMITERS

PROPORTIONAL SHIFT

### OPTIONAL

CHIPPER, BEAVER  
OR DOUBLE CARBIDE

"CHIP PRODUCTION  
ROTOR" DRUM TYPE

75CC VARIABLE  
DISPLACEMENT MOTOR

### DESIGN

17" FRONT  
EXPOSED DRUM

REPLACEABLE  
WEAR SHOES

ACCESSIBLE SERVICE  
POINTS

FIXED REAR ANVIL

### USE CASES

TOWNSHIP  
PUBLIC WORKS

RESIDENTIAL LANDSCAPING

RESIDENTIAL PROPERTY  
DEVELOPMENT



1-833-577-1847



PROMACEQUIPMENT.CA

