FECON

STUMPER







FECON.COM

800-528-3113

Stumper by Fecon stump grinder attachments give you the power to take on land clearing and maintenance while utilizing equipment you already own. A benchmark in durability for rugged stump-grinding, these attachments offer a cost-effective solution for landscaping, tree service or agricultural applications.

SPECIFICATIONS

MODEL	FST220	FST240	FST280	FST360	FST3500
Cutting Diameter	22"	24"	28"	36"	36"
Cut Depth per Pass	6"	8"	8"	12"	12"
Weight (lbs)	375	475	650	1110	1200
Max PSI	4100	4100	4100	4100	
Flow / PTO HP	8-15 GPM	ST 12-25 GPM	ST 12-25 GPM HD 25-45 GPM	30-45 GPM	40-90 PTO HP
Number of Tools	11	14	13	25	25
Carrier Compatibilty	Mini Skid Steer	3.5 - 10t / Mini Skid Steer	5-10 t / ST < 75HP SS / HD > 75HP SS	8 -10t / > 75HP SKID STEER	CLASS 2 - 3-PT HITCH 540 PTO RPM AG TRACTOR



PERFORMANCE

- Cutting wheel diameters range from 22 to 36 inches with 6 to 12 inches of cutting depth per pass to tackle everything from smalljobs to large, stubborn stumps and roots.
- A direct drive system with no belts, pulleys, gear boxes or electrical connections minimizes maintenance and keeps you grinding longer.
- Built to last with powder-coated steel weldments and quality hydraulic components.

PRODUCTIVITY

- Performs below-grade grinding for optimal stump and root mulching
- · Remove stumps yourself, maximizing job profitability.
- Oversize rakers limit the depth of each cut and prolong tooth life.



VERSATILITY

- Compatible with a wide range of carriers such as mini and standard skid steers, compact track loaders, excavators and tractors.
- Fast trailer load/unload process to get grinding more quickly.
- Low rpm grinding style reduces stumps into a small pile for easy cleanup.

SAFETY

- Features heavy-duty chip deflectors that reduce the debris field for safe operation.
- Maximum maneuverability provides ability to position carrier beside obstacles for a safer grind with exceptional visibility.
- Get to work faster with easy-to-learn controls intuitive for both new and experienced operators.
 - · Weights may vary based on options.
 - · Specifications subject to change without notice.
 - · Photographs may have been altered for marketing purposes.
 - Pictures may contain optional accessories.

- Certain guarding and features may have been removed for illustrative purposes.
- · ALWAYS RUN WITH PROPER GUARDING IN PLACE.
- $\boldsymbol{\cdot}$ SAFETY IS THE RESPONSIBILITY OF THE OPERATOR.
- · Always ensure your carrier's safety features, including ROPs & FOPs, meet your job safety requirements.